

## ServView 17 Enterprise



**A new generation KVM drawer with optional  
high-density CATx switch and IP access**

- 1280 x 1024 resolution with 16.2 million colours.
- 104 notepad keyboard with full numerical keypad.
- One-man installation slides for quick and easy install.
- High-density integrated CATx KVM switch for one or two users.
- Secure and flexible KVM over IP access.

## Enhanced KVM Drawer Design

The ServView 17 Enterprise is the optimum rack-drawer server management solution. It is economical, flexible in configuration and has a new aesthetic and ergonomic design. The rack-drawers ships as standard with both PS/2 and USB connectivity, 17" Samsung monitor, trackball mouse for enhanced precision and 104 keyboard with full numerical keypad. It is also available with most European keyboard language layouts

## Optional High-Density CATx Switch Integration

The 1U KVM drawer is available with an integrated 16-port or 32-port CATx KVM switch for high density server management environments. Servers can be placed up to 40m from the KVM switch and connected using USB or PS/2 server access modules. The integrated switch can be cascaded with further stand-alone switches to accommodate up to 128 or 256 servers depending on the model. Because it uses standard CATx cables the solution is quick, tidy and economical to install. If you need two administrators to have simultaneous access to servers choose a dual user model and locate a second KVM station up to 300m away from the switch over CATx cable using the included USB KVM extender remote.

## Optional High-Density CATx Switch Integration

For secure and flexible hardware level access to your servers from anywhere in the world, select a dual user switch with IP access. Your second user can then administer your servers using 128 bit secure IP access via a web browser, reducing travel time and server room traffic.

## TECH SPECS

**Height**— 1U  
**Width**— 19"  
**Depth**— Mounting depth from 600-920mm  
**Connectors**— Video in: (1) HD15 female; Keyboard/Mouse: (2) PS/2 6-pin mini DIN; Power: (1) IEC320  
**Dimensions**— 4.4(H)x 44.2(W)x 65(D) cm  
**Weight**— 16 kg  
**Resolution (Maximum)**— 1280 x 1024 SXGA  
**Plug-and-Play DDC**— EDID 1.3  
**Contrast Ratio**— 700:1  
**Brightness**— 300cd/m2  
**Display Colours**— 16.2 million  
**Viewing Angle**— 150° horizontal x 135° vertical  
**Internal Power Supply**— 100-240VAC, auto-sensing, IEC320  
**Operating Temperature**— 0 to 50°C  
**Storage Temperature**— 25 to 60°C

Item	Code
<b>ServView 17 Enterprise</b>	
ServView 17 Enterprise	KVT151AE-UK
ServView 17 Enterprise with 16-Port CATx Single-User Switch	KVT151AE-UK-116
ServView 17 Enterprise with 32-Port CATx Single-User Switch	KVT151AE-UK-132
ServView 17 Enterprise with 16-Port CATx Dual-User Switch	KVT151AE-UK-216
ServView 17 Enterprise with 32-Port CATx Dual-User Switch	KVT151AE-UK-232
ServView 17 Enterprise with 16-Port CATx IP Switch	KVT151AE-UK-IP16
ServView 17 Enterprise with 32-Port CATx IP Switch	KVT151AE-UK-IP32
PS/2 Server Access Module	KVT150AE-PS2
USB Server Access Module	KVT150AE-USB
16-Port Single-User CATx Switch	SW151AE-116
32-Port Single-User CATx Switch	SW151AE-132
16-Port Dual-User CATx Switch	SW151AE-216
32-Port Dual-User CATx Switch	SW151AE-232
16-Port CATx IP Switch	SW151AE-IP16
32-Port CATx IP Switch	SW151AE-IP32
<b>To cascade the ServView 17 Enterprise, order...</b>	
ServView 17 Enterprise Cascade Cable	KVT152A-CASCADE