DATA SHEET

DPMSTHUB-4P

MST HUB DISPLAYPORTTM 1.2, 4K, 4-PORT

24/7 TECHNICAL SUPPORT AT 1.877.877.2269 OR VISIT BLACKBOX.COM





OVERVIEW

MST HUB-DISPLAYPORT 1.2, 4K, 4-PORT

INTRODUCTION

The DPMSTHUB-4P 1x4 DisplayPort™ 1.2 MST Hub/Splitter provides the most cost effective and advanced DisplayPort splitter solution on the market that allows high definition video and high quality audio to be transmitted to four different locations without losing quality. It can extend the laptop or desktop to additional displays and stream independent content to each individual display, making multitasking easier and increasing your productivity. The DPMSTHUB-4P can mirror the same image or split an image to multiple displays for multi-monitor setups.

FEATURES

- DisplayPort 1.2 compliant
- Supports 4K2K@60 4:4:4 8bits
- Supports 7.1 ch surround audio
- HDCP 1.3 compliant
- Video bandwidth: 21.6 Gbps
- Supports SST or MST (Multi-Stream Transport)
- Supports xvYCC, x.v.Color & Deep Color
- Plug and Play installation

SPECIFICATIONS

MST HUB-DISPLAYPORT 1.2, 4K, 4-PORT

	SPECIFICATION CHART
SPECIFICATION	DPMSTHUB-4P
TECHNICAL	
ROLE OF USAGE)	1x4 MST Hub/Distribution Amplifier (Splitter)
DP COMPLIANCE	DisplayPort™ 1.2
HDCP COMPLIANCE	HDCP 1.3
VIDEO BANDWIDTH	21.6Gbps
VIDEO SUPPORT	4K2K@60 (4:4:4 8bits)
AUDIO SUPPORT	LPCM, AC3, DTS
ESD PROTECTION	Human body model — ±15kV [air-gap discharge] & ±8kV [contact discharge]
PCB STACK-UP	4-layer board [impedance control – differential 100Ω ; single 50Ω]
INPUT	1x DP
OUTPUT	4x DP
DP CONNECTOR	Normal type
MECHANICAL	
HOUSING	Metal enclosure
DIMENSIONS	0.6" H x 2.9" W x 4.1" D (1.6 x 7.3 x 10.5 cm)
WEIGHT	0.24 lb (.18 kg)
POWER SUPPLY	5V 1A DC
POWER CONSUMPTION	4 Watts [max]
OPERATING TEMPERATURE	32 to 104°F (0 to 40°C)
STORAGE TEMPERATURE	-4 to 140°F (-20 to +60°C)
RELATIVE HUMIDITY	20 to 90% RH (no condensation)



SPECIFICATIONS

MST HUB-DISPLAYPORT 1.2. 4K. 4-PORT





SIDE 1 VIEW SIDE 2 VIEW


WHAT'S INCLUDED

MST HUB-DISPLAYPORT 1.2, 4K, 4-PORT

- (1) DisplayPortTM MST Hub, 1-to-4
- (1) DisplayPort Cable, M/M, ~12" (~30 cm)
- (1) USB Cable for power input, USB Type A to USB Type B Micro, ~19" (~48cm)

CONNECTION DIAGRAM

MST HUB-DISPLAYPORT 1.2, 4K, 4-PORT



ORDERING INFORMATION

MST HUB-DISPLAYPORT 1.2, 4K, 4-PORT

ITEM	CODE
MST HUB-DISPLAYPORT™ 1.2, 4K, 4-PORT	DPMSTHUB-4P

D	IC	A	IM	26
u	\sim	. 🗪		T 2

Black Box Corporation shall not be liable for damages of any kind, including, but not limited to, punitive, consequential or cost of cover damages, resulting from any errors in the product information or specifications set forth in this document and Black Box Corporation may revise this document at any time without notice.

ABOUT BLACK BOX

Black Box® is a trusted IT solutions provider delivering cutting-edge technology products and world-class consulting services to businesses across the globe in every industry. The breadth of our global reach and depth of our expertise accelerate customer success by bringing people, ideas, and technology together to solve real-world business problems.

FILENAME:
DPMSTHUB-4P_ds_rev1.PDF
© COPYRIGHT 2022. BLACK BOX CORPORATION. ALL RIGHTS RESERVED.

NOTES		

TRADEMARKS

Black Box and the Black Box logo type and mark are registered trademarks of Black Box Corporation.

Any other trademarks mentioned in this document are acknowledged to be the property of the trademark owners.

